CV Circular electric duct heaters



Mech-Elec®

CV Circular electric duct heaters

Mech-Elec circular electric duct heaters are used for heating the ventilation air supplied to individual rooms and zones, with individually controlled temperatures. In correctly designed systems, they can also heat the entire building. Circular electric duct heaters are also used for preheating or reheating for ventilation units. The duct heaters are available with built-in electronic regulator or for external control. An electronic flow monitor is also available, if required.

- Seven sizes: 100 400 mm dia.
- Output range 300 W 12000 W.
- Tightness class C to EN 1751.
- A built-in electronic flow monitor is included in several of the models.
- With built-in regulator or for external control.
- Two built-in overheating protections.
- Enclosed stainless steel plain-tube elements.

Standard design

The casing is made of Aluzink-coated sheet steel, AZ 185, and the heater elements are made of stainless steel to EN 1.4541. The CV series conforms to the requirements for corrosivity class C4 (M3). The duct heaters also conform to air tightness class C to EN 1751. The junction box includes the necessary terminal blocks for the electrical connections. The duct connection is suitable for insertion mounting in circular ducts. The CV is made to degree of protection IP43, but degree of protection IP55 can also be specified (not the -MQU and -MTU versions).

Overheating protection

All CV heaters have two overheating protections, one of which is with automatic reset and the other with manual reset. On delivery, these are connected in series with the heater elements and therefore need not be connected to an external relay (except model-E; see page 13). This improves reliability and lowers the installation costs. All duct heaters (except model –R; see page 13) have the

overheating protection reset on the heater cover.

Alarm relay, designation suffix -L

All models can be equipped with a built-in relay with potential-free alarm contacts that indicate loss of power supply or tripping of the manually resettable overheatingprotection. The alarm relay is included as standard in models -MQXL and -MTXL.

Electronic flow monitor

All models with built-in control can also be supplied with a built-in electronic flow monitor. The flow monitor continually monitors the air flow and shuts down the heater if the air velocity should drop below 1.5 m/s, thus avoiding overheating. When the air velocity again exceeds 1.5 m/s, the heater will automatically be switched on. This means that the CV with built-in flow monitor meets the requirements for interlocking with the fan/air flow and can be installed without external interlocking. This ensures very simple installation.

Air tightness class C

The CV duct heater conforms to air tightness class C, which ensures that the heated air will reach its destination and will not leak out of the ventilation system – which saves energy and money.

Approvals

The duct heaters have been tested and approved by SEMKO in accordance with: LVD Directive: EN 60355-1, EN 60335-2-30, SEMKO 111-1967 mod 1-4 and SEMKO 111 FA1982. EMC Directive: EN 50081-1, EN-50082-1, EN 61000-3-2 and EN 61000-3-3 EMF Directive: EN 50366



Control

Built-in regulator

A built-in regulator ensures simple installation, e.g. due to fewer cable runs, which lowers the installation cost and reduces the risk of incorrect wiring. The regulator is electronic and controls the output across a triac by means of time proportional control (intermittent ON/OFF control). This provides very accurate temperature control. Since control is electronic, it is entirely silent and sustains a minimum of wear.

The following models are available with built-in regulator:

-MQU(L) and -MTU(L), for one sensor

Duct heater with built-in temperature regulator for room or duct sensor. The setpoint can be set on the heater cover or externally. See page 6.

-MQEM(L) and -MTEM(L), for two sensors

Duct heater with built-in temperature controller for external room sensor with setpoint adjuster. The minimum and maximum supply air temperatures are set on the duct heater circuit board. See page 8.

-MQXL and –MTXL, for 0...10V control signal

Duct heater with built-in regulator for external 0...10V control signal. See page 10.

External regulator

Some duct heaters can be specified without built-in regulator, and an external regulator must then be added. The following models are available for external regulator:

-M(L), -E(L) and -R(L)

An external temperature regulator and sensor must be provided for the duct heater. See pages 12 and 13.

Options other than the standard version

In addition to the standard design, several options are available for matching to your specific application.

Other materials

The casing can be made of stainless steel, EN 1.4301, or of stainless acid-proof material, EN 1.4404.

Anti-condensation insulation

In order to reduce the risk of condensation in the junction box if the duct heaters installed in a warm and humid area and the air in the duct is cold, the inside of the junction box is provided with additional 4mm thick insulation.

Degree of protection IP55

To special order, the duct heaters can be made to degree of protection IP55 instead of the standard IP43 version (not -MQU and -MTU).

Duct heater with an outlet temperature higher than 40°C

Available only in a rectangular version with circular connection. See "Rectangular electric duct heaters".

Sizes larger than 400 mm

Available only in a rectangular version with circular connection. See "Rectangular electric duct heaters".

Outputs higher than 12 kW

Available only in a rectangular version with circular connection. See "Rectangular electric duct heaters".

Strengthened electrical insulation

Available only in a rectangular version with circular connection. See "Rectangular electric duct heaters".

Overview of range

Size designation		CV 10	CV 12	CV 16	CV 20	CV 25	CV 31	CV 40
Diameter (Ø mm)		100	125	160*	200	250	315	400 **
Minimum air flow rate, m³/h		43	70	110	170	270	415	690
Rating	Voltage							
300 W	230 V~		Х3	X2				
400 W	230 V~	Х3						
600 W	230 V~	Х3	X۶	Х3	X2	X1		
900 W	230 V~		Х7	Χ4	X2	X2	X1	
1200 W	230 V~		Х8	Х2	Х3	X2	X1	
1500 W	230 V~		X٩	Х6	Х3	Х3	X2	
1800 W	230 V~		X ¹⁰	Х6	Χ4	Х3	X2	
2100 W	230 V~			Х7	Χ4	Х³	X2	
2700 W	230 V~			Х8				
3000 W	230 V~				Х6	Х4	Х³	X2
3000 W	400 V 2~				Х6	X4	Х³	X ²
3300 W	400 V 2~			X٩				
5000 W	400 V 2~			X ¹²	Х8	Х6	Χ4	Х3
6000 W	400 V 2~				X٩	Х7	Χ4	Х3
5000 W	400 V 3~			X12				
6000 W	400 V 3~				X9	χ7	X4	Χ3
9000 W	400 V 3~					X٩	X6	X4
12000 W	400 V 3~					X10	χ7	X ⁵

*= Also available with 150 mm dia. Delivered without rubber seals **=Also available with 355 mm dia. Delivered without rubber seals.

1= See pressure drop curve 1 2= See pressure drop curve 2

7= See pressure drop curve 7 8= See pressure drop curve 8

- 3= See pressure drop curve 3
- 9= See pressure drop curve 9 10= See pressure drop curve 10 4= See pressure drop curve 4
- 5= See pressure drop curve 5
 - 11= See pressure drop curve 11 12= See pressure drop curve 12
- 6= See pressure drop curve 6

Pressure drop graph



2

Installation

The duct heaters can be installed in either a horizontal or a vertical duct. The air must flow through the duct heater in the direction of the arrow shown on the duct heater. In a horizontal duct, the junction box may face either upwards or at 90° to either side. Installation with the junction box at the bottom is not permissible. The distance to or from a duct bend, fan, damper or the like must be at least twice the connection diameter.



Interlock with fan/air flow rate

Electric duct heaters must always be installed so that they are interlocked either with the fan that delivers the air into the duct or with the air flow rate through the heater. The power supply to the duct heater must be isolated if the fan/ air flow is switched off.

The -MQU and -MQEM models and the -MQXL with built-in electronic flow monitor conform to the requirement for interlocking with the fan/air flow rate and can be installed without external interlocking.

For other models, this function must be connected on the incoming power supply to the duct heater or, if the heater has a built-in regulator, directly to the regulator.

Dimensions in mm

Minimum air velocity and outlet air temperature

The duct heaters are designed for a minimum air velocity of 1.5 m/s and a maximum operating outlet air temperature of 40° C (for higher temperatures, see "Rectangular electric duct heaters").

Ambient air temperatures for duct heaters: Without built-in control equipment = 40°C max. With built-in control equipment = 30°C max.

The following formula can be used for calculating the air velocity:

$$V = \frac{Q}{3600 \times A}$$

$$V = \text{air velocity, m/s}$$

$$Q = \text{air flow rate, m}^{3}/h$$

$$A = \text{cross-section area of duct heater, m}^{2}$$

A = $\frac{\pi \times D^2}{4}$ D = diameter of duct heater, Øm

Power demand

The air flowing through the duct heater is heated in accordance with the following formula:

	P = rating in W
$P = Q \times 0.36 \times \Delta t$	Q = air flow rate in m^{3}/h
	Δt = temperature rise in °C





CV Circular electric duct heater with built-in control equipment for a room or a duct sensor

The built-in control unit simplifies installation, e.g. by fewer cable runs. This, in turn, lowers the installation cost and reduces the risk of incorrect wiring.

The duct heater operates with an external room or duct sensor. The temperature is set on the heater cover or on an external setpoint adjuster.

- MQU

Duct heater with built-in temperature regulator for room or duct sensor. The heater can be reset for external setpoint adjustment or for setpoint adjustment on the heater cover. The -MQU model also has a built-in electronic flow monitor which simplifies the installation since it can be installed "stand alone".

The sensor and the nearest setpoint adjuster are available as separate accessories.

- MTU

Same model as above but without built-in electronic flow monitor.

- MQUL and -MTUL

Same models as above but with built-in relay with potentialfree alarm contacts that indicate loss of power supply or tripping of the manually resettable overheating protection.



Project design/ordering

Descriptive text for - MQU

Mech-Elec type CV – MQU duct heater with casing of Aluzink-coated sheet steel, AZ 185, and stainless steel heater element, En 1.4541. The duct heater conforms to tightness class C and corrosivity class C4. Built-in electronic flow monitor. Control takes place by a built-in temperature regulator for room or duct sensor. Setpoint adjustment takes place externally or on the heater cover. The sensor and any external setpoint adjuster must be ordered separately.

Descriptive text for – MTU Mech-Elec type CV – MTU duct heater with ccasing of

Aluzink-coated sheet steel, AZ 185, and stainless steel heater element, En 1.4541. The duct heater conforms to tightness class C and corrosivity class C4. Control takes place by a built-in controller for room or duct sensor. Setpoint adjustment is carried out externally or on the heater cover. The sensor and any external setpoint adjuster must be ordered separately.

Type designation	<u>CV 16 - 50 - 2 MQUL</u>
(example)	
Size designation, see page 4	
Rating in watt x 100 —————————————————————————————————	
Voltage 1=230 V~ 2=400 V 2~ 3=400 V 3~	
Type of control (-MQU/-MQUL/-MTU/ MTUL, see above)	



2

Accessories

There are several sensor/setpoint combinations for the CV -MQU(L)/-MTU(L). Five typical cases are presented here. For particulars of sensors, see page 15.

Duct sensor

Alt 1 Duct sensor with setpoint adjustment on the duct heater cover.

Alt 2 Duct sensor with external setpoint adjustment.



TG-K330 as duct sensor.



TG-K330 as duct sensor.



The setpoint is adjusted manually on the duct heater cover.



TG-R430 as setpoint potentiometer.

Room sensor

Alt 3 Room sensor with setpoint adjustment.



TG-R430 both as setpoint potentiometer and room sensor.



TG-R530 (IP30) or TG-R630 (IP54) as room sensor.

Alt 4 Room sensor with external setpoint adjustment.



TG-R430 as setpoint potentiometer.

Alt 5 Room sensor with setpoint adjustment on the duct heater cover.



TG-R530 (IP30) or TG-R630 (IP54) as room sensor.



The setpoint is adjusted manually on the duct heater cover.

CV Circular electric duct heater with built-in temperature regulator for two sensors – one room sensor and one min/max supply air sensor.

The built-in control unit simplifies installation, e.g. by fewer cable runs. This, in turn, lowers the installation cost and reduces the risk of incorrect wiring. The duct heater operates with an external room or duct sensor. The temperature is set on an external setpoint adjuster.

- MQEM

Duct heater with built-in temperature regulator for room sensor with setpoint adjuster type TG-R430 and supply air sensor TG-K360. The required room air temperature is set on the TG-R430. The minimum and maximum supply air temperatures are set on the duct heater circuit board. The -MQU model also has a built-in electronic flow monitor which simplifies the installation since it can be installed "stand alone".

The sensor and the nearest setpoint adjuster are available as separate accessories.

- MTEM

Same model as above but without built-in electronic flow monitor.

- MQEML and -MTEML

Same models as above but with built-in relay with potential-free alarm contacts that indicate loss of power supply or tripping of the manually resettable overheating protection.



Project design/ordering

Descriptive text for – MQEM

Mech-Elec type CV – MQEM duct heater with casing of Aluzink-coated sheet steel, AZ 185, and stainless steel heater element,EN 1.4541. The duct heater conforms to tightness class C and corrosivity class C4. Built-in electronic flow monitor. Control takes place by built-in temperature regulator for room sensor with setpoint adjuster and separate supply air sensor. The sensor and external setpoint adjuster must be ordered separately.

Descriptive text for – MTEM

Mech-Elec type CV –MTEM duct heater with casing of Aluzink-coated sheet steel,Az 185, and heater element of stainless steel, En 1.4541. The duct heater conforms to tightness class C and corrosivity class C4. Control takes place by built-in temperature regulator for room sensor with setpoint adjuster and separate supply air sensor. The sensor and external setpoint adjuster must be ordered separately.

(example)
Size designation, see page 4
Rating in watt x 100
Voltage 1=230 V~ 2=400 V 2~ 3=400 V 3~
Type of control (-MQEM/-MQEML/-MTEM/ MTEML; see above)

Accessories

There are several sensor/setpoint combinations for the CV -MQEM(L)/-MTEM(L). Three typical cases are presented here. For particulars of sensors, see page 15.

Duct sensor

Alt 1 Duct sensor with external setpoint adjustment.



TG-K330 duct sensor as exhaust air sensor.



TG-R430 as setpoint potentiometer.



TG-K360 duct sensor for min/max supply air temperature.

Room sensor

Alt 2 Room sensor with setpoint potentiometer.



TG-R430 as both setpoint potentiometer and room sensor.



TG-K360 duct sensor for min/max supply air temperature.

Alt 3 Room sensor and separate setpoint potentiometer.



TG-R530 (IP30) or TG-R630 (IP54) as room sensor.



TG-R430 as setpoint potentiometer.



TG-K360 duct sensor for min/max supply air temperature.

CV Circular electric duct heater with built-in control equipment for external 0...10 V control signal

The built-in control unit simplifies installation, e.g. by fewer cable runs. This, in turn, lowers the installation cost and reduces the risk of incorrect wiring.

- MQXL

Duct heater with built-in regulator for 0...10 V control signal.

The -MQXL model also has a built-in electronic flow monitor which simplifies the installation since it can be installed "stand alone".

The heater has a built-in relay with potential-free alarm contacts that indicate loss of power supply or tripping of the manually resettable overheating protection.

- MTXL

Same model as above but without built-in electronic flow monitor.



Descriptive text for -MTXL

Mech-Elec type CV – MTXL duct heater with casing of

Aluzink-coated sheet steel, AZ 185, and stainless steel

heater element, EN 1.4541. The duct heater conforms

that indicate loss of power supply or tripping of the

manually resettable overheating protection. Control

takes place by a built-in regulator for external 0...10 V

to tightness class C and corrosivity class C4.

Built-in relay with potential-free alarm contacts

Project design/ordering

Descriptive text for – MQXL

Mech-Elec type CV – MQXL duct heater with casing of Aluzink-coated sheet steel, AZ 185, and stainless steel heater element, EN 1.4541. The duct heater conforms to tightness class C and corrosivity class C4. Builtin electronic flow monitor and built-in relay with potential-free alarm contacts that indicate loss of power supply or tripping of the manually resettable overheating protection. Control takes place by a builtin regulator for external 0...10 V control signal.

in regulator for external 010 V control signal.	control signal.
Type designation (example)	<u>CV 16 - 50 - 2</u> <u>MQXL</u>
Size designation, see page 4	
Rating in watt x 100 —————————————————————————————————	
Voltage 1=230 V~ 2=400 V 2~ 3=400 V 3~	
Type of control (-MQXL/-MTXL; see above)	

Control with accessories

There are several ways of controlling a CV -MQXL/-MTXL.

Master system



Ventilation unit that has built-in control with a 0...10V output for a reheater coil



0...10V regulator control



CV Circular electric duct heater for external control equipment

Mech-Elec electric duct heaters for external control must be equipped with an external temperature regulator. These can be mounted on a wall or in an equipment cubicle. Regulators and sensors must be ordered separately (see pages 14 and 15).

- M

Suitable control by PULSER or TTC type regulator. The overheating protection is reset manually on the duct heater cover. Ratings up to and including 9000 W.

- ML

Same model as above but with built-in relay with potentialfree alarm contacts that indicate loss of power supply or tripping of the manually resettable overheating protection.



Project design/ordering

Descriptive text for - M

Mech-Elec type CV – M duct heater with casing of Aluzink-Mech-Elec type CV – ML duct heater with casing of Aluzinkcoated sheet steel, AZ 185, and stainless steel heater element, EN 1.4541. Control takes place by an external regulator and sensor that must be ordered separately.

Descriptive text for – ML

coated sheet steel, AZ 185, and stainless steel heater element, EN 1.4541. Built-in relay with potential-free alarm contacts that indicate loss of power supply or tripping of the manually resettable overheating protection. Control takes place by an external regulator and sensor that must be ordered separately.

Type designation (example)	<u>CV 16 - 50 - 2 ML</u>
Size designation, see page 4	
Rating in watt x 100	
Voltage 1=230 V~ 2=400 V 2~ 3=400 V 3~	
Type of control (-M/-ML; see above)	

CV Circular electric duct heater for external control equipment

Mech-Elec electric duct heaters for external control must be equipped with an external temperature regulator. These can be mounted on a wall or in an equipment cubicle. Regulators and sensors must be ordered separately (see pages 14 and 15).

- R

The built-in manual overheating protection is manually reset remotely by an external type RSI/RSU reset button with indicating lamp.

The lamp will light up when the overheating protection has tripped.

For 230 V, a PULSER 220 R can be used which, in addition to the ordinary control functions, also has a built-in reset button and indicating lamp.

For 400 V, a PULSER or TTC and an external RSI/RSU reset button are used.

- E

Suitable control by type TTC regulator.

The built-in manual overheating protection is reset on the duct heater cover. The overheating protections are single-pole and must be connected to an external operating circuit.

Rating of 12000 W.



Project design/ordering

Descriptive text for - R

coated sheet steel, AZ 185, and stainless steel heater element, EN 1.4541. Control takes place by an external regulator and sensor that must be ordered separately.

Descriptive text for – E

Mech-Elec type CV -R duct heater with casing of Aluzink- Mech-Elec type CV -E duct heater with casing of Aluzinkcoated sheet steel, AZ 185, and stainless steel heater element, EN 1.4541. Control takes place by an external regulator and sensor that must be ordered separately.

Type designation (example)	<u>CV 16</u> - <u>50</u> - <u>2</u> <u>R</u>
Size designation, see page 4	
Rating in watt x 100	
Voltage 1=230 V~ 2=400 V 2~ 3=400 V 3~	
Type of control (-E/-R; see above)	

2

Mech-Elec

Electric heater regulators





PULSER

PULSER D

PULSER DSP

PULSER Series

PULSER is a series of electric heater regulators that regulate the output by means of time proportional control (intermittent ON/OFF control). This provides very accurate temperature control.

Degree of protection: Max. load:

IP30 (PULSER D IP20) 230V AC, 3200 W 400V, 2-phase, 6400 W

PULSER

The PULSER operates with one sensor, i.e. the built-in room sensor or an external sensor, e.g. a duct sensor. Automatic switching between 230V AC and 400V, 2-phase.

PULSER D

Same characteristics as the PULSER, but for DIN rail mounting.

PULSER DSP

Samma egenskaper som PULSER men med display samt maxbelastning 230 V~ 2300 W och 400 V 2~ 4000 W

PULSER M

With an additional input for Min./Max sensor in the supply air duct*. PULSER M then controls the room temperature, at the same time maintaining a minimum supply air temperature.

Automatic switching between 230V AC and 400V, 2-phase. *Use duct sensor/min. sensor TG-K330.

PULSER ADD

PULSER ADD has no sensor of its own but is under slave control from another PULSER and operates in parallel with it. This means that two duct heaters can be controlled by the sensor. Automatic resetting between 230 V~ och 400 V 2~.

PULSER 220 R

The PULSER -R operates with one sensor, i.e. the built-in room sensor or an external sensor, e.g. a duct sensor. It is specially adapted for operating together with a CV type -R duct heater for 230 V~. The PULSER -R is provided with a reset button and a lamp that lights up when the overheating protection has tripped.



TTC 40F

TTC Series

Electric heater regulators that control the output by time proportional control (intermittent ON/OFF control), which provides very accurate temperature control. The setpoint is preset either on the regulator or externally.

The TTC series has terminals for external main sensor and min./max. sensor. Use the TG-K360 as min./max. sensor. Alternatively, the TTC series can be controlled by an external 0...10V signal.

TTC 2000

For wall mounting.	
Maximum installed power:	17 kW, 400V, 3-phase
Automatic switching:	210V AC - 415V 3-phase
Degree of protection:	IP30

TTC 25 and TTC 40F

For mounting on a DIN rail in an electrical cubicle. 210V AC - 415V 3-phase Automatic switching: Degree of protection: IP20

Maximum power at the terminals:				
TTC 25:	25 A, 400 V, 17 kW			
TTC 40F:	40 A, 400 V, 27 kW			

PULSER 220 X010 and PULSER 380 X010

These regulators are controlled by an external 0...10 V control signal. Supply voltage 230 V~ and 400 V 2~ respectively.

CIRCULAR ELECTRIC DUCT HEATERS REGULATORS AND ACCESSORIES

Mech-Elec®

Accessories

	Product	Range	Degree of protection	
0	Duct sensor TG-K330	0-30°C	IP20	
6	Duct sensor TG-K360 Min./Max. sensor for TTC-Series	0-60°C	IP20	
1	Room sensor TG-R430 with setpoint adjustment	0-30°C	IP30	
-	Room sensor TG-R530	0-30°C	IP30	
4	Room sensor TG-R630	0-30°C	IP54	
15	Pressure switch DTV200 incl. connection kit	20 - 300 Pa Max. 5A, 230 V AC	IP54	
	Pressure switch AFS-222	10 - 3000 Pa Max. 15A, 230 V AC	IP20	
	Connection kit	For AFS-222		
	RSI/RSU reset button.	For remote resetting of overheating protection in the CV type -R	IP20	